

Tenfly MNXL22F1

Tenfly 21.5-inch FHD Basic Monitor

- 21.5 Inch FHD (1920×1080) IPS monitors with thin bezels and 100Hz refresh rate
- 1000:1 contrast ratio (Typ.) for deeper blacks
- 250 cd/m² brightness
- Dual HDMI ports + DC input
- Low blue light + flicker-free technology
- ≤0.5W standby power consumption
- VESA 75×75mm mount (tool-free disassembly)



Overview

As a computer monitor wholesale suppliers, Tenfly provides a range of displays. MNXL22F1 Monitor's IPS display provides visual enjoyment with an ultra-wide viewing angle that delivers high color accuracy and image quality. Its 3-sided NearEdgeless bezel design lets you focus on your work with fewer distractions. Rich display quality is enhanced with 99% sRGB color for an impressive viewing experience. Comfort is key with the MNXL22F1 Monitor, boasting Natural Low Blue Light technology that minimizes visual fatigue and strain and protects your eyes.

Features and Benefits

■ 100Hz Fluid Experience

Going beyond the standard 60Hz, the 100Hz refresh rate delivers exceptionally smooth scrolling, animations, and video conferencing visuals. It significantly reduces eye strain from extended work.

■ 99% sRGB Color Accuracy

Ensure color reproduction. Ideal for daily design tasks, image editing, and multimedia presentations, maintaining professional visual output.

■ Eye-Comfort Technology

Low blue light technology and flicker-free backlight provide necessary protection for employees who face screens all day.

■ Flexible Deployment & Installation

Adopting a standard VESA 75×75mm mount, it can be easily integrated with various stands and arms. It saves desk space and creates a neat and efficient workspace.



Specifications

| | |
|---------------------------|--|
| Screen Size | 21.5 inch |
| Aspect Ratio | 16:9 |
| Panel Type | IPS |
| Resolution | 1920*1080 |
| Refresh Rate | 100Hz |
| Brightness | 250 cd/ m ² |
| Contrast Ratio | 1000:1 |
| Backlight | ELED |
| Viewing Angle | 178°/ 178° |
| Response Time | 14ms |
| I/O Ports (Standard) | DC+2HDMI |
| VESA Dimension | 75*75mm |
| Adapter Type | External Power Adapter |
| Adapter Power | 24W (12V 2A) |
| Standby Power Consumption | ≤0.5W |
| Dimensions with Stand | 494*371.76*209.99mm |
| Dimensions without Stand | 494*286.37*38.79mm |
| Dimensions with Package | 569*367*140mm |
| Weight with Package | 2.4Kg |
| Weight without Package | 3.2Kg |
| Temperature | Working:0°C~40°C; Storage:-20°C~60°C |
| Humidity | Working:10~85%RH; Storage:5~90% (No Freezing under 40°C) |
| Altitudes | ≤5000m |
| Package Contents | LCD display, Power Adapter with Power Cable, HDMI Cable, USER Manual |
| Warranty | Three-year limited warranty on parts |